

Colorbond display units



1URC-444-BR



2URC-976-BR



3URC-1507-BR

Model	Ltr	Unit Size W x D x H (mm)
1URC-444-BR	444	635 x 762 x 2040
2URC-976-BR	976	1260 x 762 x 2040
3URC-1507-BR	1507	1880 x 762 x 2040

Product Features

- Colorbond interior & exterior with light box
- +2°C to +5°C ambient temperature of +42°C
- Self contained Danfoss motor
- On castors
- Digital adjustable temperature controller
- R134A green refrigerant gas
- CFC & HCFC free
- Forced air circulation
- Self closing & self holding doors
- Lockable doors
- Arc angled interior
- Polyurethane insulation to improve cooling & reduce energy consumption
- Heated doors to prevent sweating
- Automatic defrost heater
- 5 PVC shelves per door

Upright stainless steel solid door chiller models



1URS-CH-505



2URS-CH-1103



3URS-CH-1701

Model	Ltr	Unit Size W x D x H (mm)
1URS-CH-505	505	660 x 762 x 2040
2URS-CH-1103	1103	1300 x 762 x 2040
3URS-CH-1701	1701	1940 x 762 x 2040

Product Features

- Stainless steel interior & exterior
- +2°C to +5°C ambient temperature of +42°C
- Self contained Danfoss motor
- On castors
- Digital adjustable temperature controller
- R134A green refrigerant gas
- CFC & HCFC free
- Forced air circulation
- Recessed embedded handles
- Self closing doors
- Lockable doors
- Arc angled interior
- Polyurethane insulation to improve cooling & reduce energy consumption
- Heated doors to prevent sweating
- Automatic defrost heater
- 4 PVC shelves per door

Upright stainless steel solid door freezer models



1URS-FR-505



2URS-FR-1103



3URS-FR-1701

Model	Ltr	Unit Size W x D x H (mm)
1URS-FR-505	505	660 x 762 x 2040
2URS-FR-1103	1103	1300 x 762 x 2040
3URS-FR-1701	1701	1940 x 762 x 2040

Product Features

- Stainless steel interior & exterior
- -15°C to -18°C with an ambient temperature of +42°C
- Self contained Danfoss motor
- On castors
- Digital adjustable temperature controller
- R404A green refrigerant gas
- CFC & HCFC free
- Forced air circulation
- Recessed embedded handles
- Self closing doors
- Lockable doors
- Arc angled interior
- Polyurethane insulation to improve cooling & reduce energy consumption
- Heated doors to prevent sweating
- Automatic defrost heater
- 4 PVC shelves per door

Counter stainless steel 2 solid door chiller models



CCH-SD-1200



CCH-SD-1500



CCH-SD-1800

Model	Ltr	Unit Size W x D x H (mm)
CCH-SD-1200	278	1200 x 762 x 900
CCH-SD-1500	385	1500 x 762 x 900
CCH-SD-1800	500	1800 x 762 x 900

Product Features

- Stainless steel interior & exterior
- +2°C to +5°C with an ambient temperature of +42°C
- Self contained Danfoss motor
- On 150mm adjustable legs
- Digital adjustable temperature controller
- R134A green refrigerant gas
- 240V 10amp
- Recessed embedded handles
- Self closing doors
- Arc angled interior
- Polyurethane insulation to improve cooling & reduce energy consumption
- Heated doors to prevent sweating
- Automatic defrost heater
- 2 PVC shelves per door

Counter stainless steel 3 solid door chiller models



CCH-SD-2100



CCH-SD-2400

Model	Ltr	Unit Size W x D x H (mm)
CCH-SD-2100	570	2100 x 762 x 900
CCH-SD-2400	720	2400 x 762 x 900

Product Features

- Stainless steel interior & exterior
- +2°C to +5°C ambient temperature of +42°C
- Self contained Danfoss motor
- On castors or 150mm adjustable legs
- Digital adjustable temperature controller
- R134A green refrigerant gas
- CFC & HCFC free
- Forced air circulation
- Recessed embedded handles
- Self closing doors
- Arc angled interior
- Polyurethane insulation to improve cooling & reduce energy consumption
- Heated doors to prevent sweating
- Automatic defrost heater
- 2 PVC shelves per door

Counter stainless steel 2 solid door freezer models



CFR-SD-1200



CFR-SD-1500



CFR-SD-1800

Model	Ltr	Unit Size W x D x H (mm)
CFR-SD-1200	278	1200 x 762 x 900
CFR-SD-1500	385	1500 x 762 x 900
CFR-SD-1800	500	1800 x 762 x 900

Product Features

- Stainless steel interior & exterior
- -15°C to -18°C with an ambient temperature of +42°C
- Self contained Danfoss motor
- On castors or 150mm adjustable legs
- Digital adjustable temperature controller
- R404A green refrigerant gas
- CFC & HCFC free
- Forced air circulation
- Recessed embedded handles
- Self closing doors
- Arc angled interior
- Polyurethane insulation to improve cooling & reduce energy consumption
- Heated doors to prevent sweating
- Automatic defrost heater
- 2 PVC shelves per door

Counter stainless steel 3 solid door freezer models



CFR-SD-2100



CFR-SD-2400

Model	Ltr	Unit Size W x D x H (mm)
CFR-SD-2100	570	2100 x 762 x 900
CCH-SD-2400	720	2400 x 762 x 900

Product Features

- Stainless steel interior & exterior
- -15°C to -18°C with an ambient temperature of +42°C
- Self contained Danfoss motor
- On castors or 150mm adjustable legs
- Digital adjustable temperature controller
- R404A green refrigerant gas
- CFC & HCFC free
- Forced air circulation
- Recessed embedded handles
- Self closing doors
- Arc angled interior
- Polyurethane insulation to improve cooling & reduce energy consumption
- Heated doors to prevent sweating
- Automatic defrost heater
- 2 PVC shelves per door

Counter dual temperature stainless steel 2 solid door chiller & freezer models



C2-DT-1200



C2-DT-1500



C2-DT-1800

Model	Ltr	Unit Size W x D x H (mm)
C2-DT-1200	120 (chiller) 120 (freezer)	1200 x 762 x 900
C2-DT-1500	156 (chiller) 156 (freezer)	1500 x 762 x 900
C2-DT-1800	213 (chiller) 213 (freezer)	1800 x 762 x 900

Product Features

- Stainless steel interior & exterior
- +2°C to +5°C with an ambient temperature of +42°C (chiller)
- -15°C to -18°C with an ambient temperature of +42°C (freezer)
- Self contained Danfoss motor
- 1 door chiller & 1 door freezer
- On castors or 150mm adjustable legs
- Digital adjustable temperature controller
- R404A green refrigerant gas
- CFC & HCFC free
- Forced air circulation
- Recessed embedded handles
- Self closing doors
- Arc angled interior
- Polyurethane insulation to improve cooling & reduce energy consumption
- Heated doors to prevent sweating
- Automatic defrost heater
- 2 PVC shelves per door

Counter dual temperature stainless steel 3 solid door chiller & freezer models



C3-DT-2100



C3-DT-2400

Model	Ltr	Unit Size W x D x H (mm)
C3-DT-2100	368 (chiller) 215 (Freezer)	2100 x 762 x 900
C3-DT-2400	441 (chiller) 251 (freezer)	2400 x 762 x 900

Product Features

- Stainless steel interior & exterior
- +2°C to +5°C with an ambient temperature of +42°C (chiller)
- -15°C to -18°C with an ambient temperature of +42°C (freezer)
- Self contained Danfoss motor
- 2 door chiller & 1 door freezer
- On castors or 150mm adjustable legs
- Digital adjustable temperature controller
- R404A green refrigerant gas
- CFC & HCFC free
- Forced air circulation
- Recessed embedded handles
- Self closing doors
- Arc angled interior
- Polyurethane insulation to improve cooling & reduce energy consumption
- Heated doors to prevent sweating
- Automatic defrost heater
- 2 PVC shelves per door

Upright 2 full solid door dual temp series



UR-DTB-2SD

Model	Ltr	Unit Size W x D x H (mm)
UR-DTB-2SD	505 (chiller) 505 (freezer)	1300 x 762 x 2040

Product Features

- Stainless steel exterior and interior
- +2°C to +5°C with an ambient temperature of 42°C (chiller)
- -15°C to -18°C with an ambient temperature of 42°C (freezer)
- Self contained Danfoss motors
- 1 door Chiller & 1 door freezer
- On castors
- Digital adjustable temperature controller
- R134A green refrigerant gas
- R404A green refrigerant gas
- 240V 10amp
- CFC & HCFC free
- Fan forced air circulation
- Self closing doors
- Polyurethane insulation to improve cooling & reduce energy consumption
- Heated doors to prevent sweating
- Automatic defrost heater
- 4 adjustable PVC shelves per door

Upright 3 full solid door dual temp series



UR-DTB-3SD

Model	Ltr	Unit Size W x D x H (mm)
UR-DTB-3SDCF	1010 (chiller) 550 (freezer)	1940 x 762 x 2040

Product Features

- Stainless steel exterior and interior
- +2°C to +5°C with an ambient temperature of 42°C (chiller)
- -15°C to -18°C with an ambient temperature of 42°C (freezer)
- Self contained Danfoss motors
- 2 doors chiller & 1 door freezer
- On castors
- Digital adjustable temperature controller
- R134A green refrigerant gas
- R404A green refrigerant gas
- 240V 10amp
- CFC & HCFC free
- Fan forced air circulation
- Self closing doors
- Polyurethane insulation to improve cooling & reduce energy consumption
- Heated doors to prevent sweating
- Automatic defrost heater
- 4 adjustable PVC shelves per door